

2/RR 18

Process and plant for the separation and purification of diphenols in the phenol and phenol derivatives industry

5           The present invention relates to a process for  
the separation and purification of crude mixtures  
essentially comprising hydroquinone and resorcinol,  
optionally tars and optionally catechol, in order to  
extract therefrom first the hydroquinone and secondly  
10 the resorcinol, and the catechol, when it is present,  
and optionally to purify these various compounds. It  
also relates to the plants which allow this process to  
be implemented.

          The phenol and phenol derivatives industry  
15 generates large volumes of byproducts comprising, among  
a great variety of tars, the para, ortho and meta  
derivatives of dihydroxybenzene. They are hydroquinone  
(para compound: 1,4-dihydroxybenzene), catechol or  
pyrocatechin (ortho compound: 1,2-dihydroxybenzene) and  
20 resorcinol or resorcin (meta compound:  
1,3-dihydroxybenzene).

          These three compounds have an added value but  
their extraction from such complex mixtures is not  
without presenting problems of a technical nature and  
25 an economic nature. Moreover, hydroquinone and  
resorcinol are isomers which are particularly difficult  
to separate.

          FR-A-2 467 185 discloses a process for the  
separation and purification of resorcinol and  
30 hydroquinone involving stages of distillation and of  
recrystallization by using a solvent such as water or  
an organic solvent. According to one alternative form,  
this process provides distillation stages using steam  
for entraining the hydroquinone in the form of  
35 hydroquinone vapor. This process uses a third solvent  
which subsequently has to be removed, which requires  
additional stages and devices, for example for

- 2 -

filtration and for drying, and optionally for reprocessing or recycling the solvent.

5 An object of the present invention, which relates in particular to the separation and the purification of diphenols in the phenol and phenol derivatives industry, is to provide an appropriate method and plant which make it possible to separate and to purify, under favorable economical conditions, hydroquinone and resorcinol from a crude mixture.

10 Another object of the invention is to make possible the separation and the purification of first hydroquinone and secondly resorcinol from a crude mixture comprising other compounds, in particular tars, and/or optionally catechol, and also to separate and purify the catechol optionally present.

15 Another object of the invention is to provide such a process which can be operated largely continuously.

20 Yet another object of the invention is to provide such a process and plant which make it possible to obtain hydroquinone, resorcinol and catechol having a high purity, in particular of greater than 98%, preferably than 99%, indeed even greater than or equal to 99.5%.

25 Yet another object of the invention is to provide such a process which does not require the use of a third solvent.

30 These objects are achieved in accordance with the invention by a process for the purification of a crude mixture comprising hydroquinone and resorcinol, optionally tars, and optionally catechol, in which process the crude mixture is subjected to a series of distillation stages, preferably carried out continuously, comprising:

35 (i) an optional first distillation stage (I) designed to produce catechol as distillation top product; this stage is carried out when the crude mixture comprises catechol, in particular

- when the content of catechol in the crude mixture exceeds 2% inclusive,
- (ii) the distillation bottom product obtained under (i) where the crude mixture in the absence of stage (I) is subjected to a distillation stage (II) designed to produce, as distillation top product, a resorcinol-rich fraction comprising resorcinol, essentially, and hydroquinone,
- 5
- (iii) the distillation bottom product obtained under (ii) is subjected to a distillation stage (III) designed to produce, as distillation top product, a hydroquinone-rich fraction comprising hydroquinone, essentially, and resorcinol,
- 10
- 15

and then the hydroquinone-rich fraction and/or the resorcinol-rich fraction is/are subjected to a refining stage (IV, V) in order to extract the hydroquinone and/or the resorcinol.

20 In order to improve the yield for the recovery of hydroquinone from the crude mixture, it is preferable to precede stages (I) and/or (II) by at least one predistillation "detarring" stage (1) which makes it possible to remove the tars as distillation

25 bottom product. It is even preferable then to redistil this distillation bottom product in at least one second preliminary detarring stage (1') and to recover the distillation top product, capable of comprising a certain amount of the desired compounds. The

30 distillation [lacuna] or the two (or more) distillation top products thus obtained are conveyed as feed mixture to stage (I), if such a stage is provided, or stage (II), in the contrary case. More preferably, these preliminary stages are carried out continuously with

35 the distillation stages which follow.

The mixtures to which the process applies are mainly those comprising in particular, with respect to the total mixture:

- 4 -

- from 20 to 60%, in particular from 30 to 50%, by weight of hydroquinone,
- from 2 to 20%, in particular from 2 to 15%, by weight of resorcinol,
- 5 - from 0 to 20%, in particular from 5 to 15%, by weight of catechol,
- the remainder being formed of various compounds, essentially tars.

The "detarring" distillation stages (1, 1') can  
10 be carried out with scraped falling film devices of conventional design or short path devices. However, the use of multistage columns is not ruled out (see, e.g., column (III)). The aim is simply to remove as much as possible of the tars without a significant loss of the  
15 desired compounds.

If stages (1 and 1') are not provided, it is preferable to use columns (I) and (II) with antifouling packings in order to limit the fouling thereof by the tars. Such packings are fully known to a person skilled  
20 in the art.

Stage (I) is targeted simply at extracting the catechol and thus at obtaining, as top product, catechol with a purity which is as high as possible. The aim in particular is to obtain a fraction  
25 comprising at least 98%, preferably at least 99%, of catechol.

The term "rich" as used above for stages (II) and (III) is understood to mean that the compound targeted is the major component, the other compound  
30 being a minor component but present in a sufficient amount to subsequently make possible the refining. A person skilled in the art is entirely in a position to determine by routine tests the ranges of ratios, basing himself on the crystallization curve of a resorcinol/  
35 hydroquinone mixture, in order to determine the ratios corresponding to the range of the eutectics. From this information, by varying the operating parameters of the columns, it is possible to achieve conditions such that

the rich fractions have a ratio which appears on either side of this range, as is known per se, which will allow the subsequent implementation of the refining.

The operating conditions of stages (II) and  
5 (III) are thus related. Each is targeted at the production, as distillation top product (as column top product), of a hydroquinone/resorcinol mixture which is compatible with the subsequent refining stage.

It is thus preferable for stage (III) to result  
10 in a mixture comprising:

- from 75 to 95%, preferably from 85 to 92%, of resorcinol,
- from 5 to 25%, preferably from 8 to 15%, of hydroquinone.

15 (Possible residues of other compounds, e.g. catechol, which remain minor components, are not taken into account).

These operating conditions make it possible to ensure, during stage (III), the production as  
20 distillation top product of a mixture comprising in particular:

- from 75 to 98%, preferably from 85 to 97.5%, of hydroquinone,
- from 2 to 25%, preferably from 2.5 to 15%, of  
25 resorcinol.

(Here again, possible residues of other compounds which may be present in negligible amounts are not taken into account).

From this information, a person skilled in the  
30 art is fully in a position to choose the means to be employed according to the starting mixture. The following should simply be noted. The size (in particular the diameter) of the distillation columns depends on the circulating stream and on the internal  
35 pressure. They will thus be dimensioned mainly according to the flow rate of the mixture to be treated. The internal parameter which is the number of theoretical stages is determined in particular by the

composition (ratios) of the entering mixture and the purity or the composition of the mixture which has to be obtained as distillation top product and as distillation bottom product. It will be specified that  
5 the columns may without distinction be packed with plates or with stacked packing, as is fully known to a person skilled in the art. The plant having been determined, a person skilled in the art adjusts the operating parameters of the columns.

10 Thus, the distillation column (I) can advantageously but not limitingly be a column having the following specifications:

- number of theoretical stages: from 5 to 40, preferably from 10 to 30;
- 15 - reflux ratio R of between 1 and 10, preferably between 2 and 5.

The distillation column (II) can advantageously but not limitingly be a column having the following specifications:

- 20 - number of theoretical stages: from 10 to 85, preferably from 15 to 40,
- reflux ratio R of between 1 and 35, preferably between 5 and 25.

The distillation column (III) can very simply  
25 be a column of type (1) or alternatively a column having the following specifications:

- number of theoretical stages: from 1 to 10, preferably from 1 to 5,
- reflux ratio R of between 0.5 and 5, preferably  
30 between 1 and 2.

The refining is carried out batchwise using devices which make possible liquid/solid separation (draining, zone melting) and which are dimensioned according to the volume to be treated and their number.  
35 The choice of the type of device is not critical either. They can, for example, be conventional drainers or other refining devices, for example those sold under the name Proapt (registered trademark). It is possible,

for example, to use drainers of the type with a vertical cylindrical tubular exchanger.

The treatment of the rich fractions in these devices is carried out essentially according to the  
5 four following phases:

- phase 1 corresponds to the slow crystallization of the charged mixture
- phase 2 corresponds to the cold draining of the eutectic (resorcinol and hydroquinone mixture)
- 10 - phase 3 corresponds to the hot draining recovered during the reheating phase until the desired purity is obtained
- phase 4 corresponds to the melting-recovery of the pure product.

15 The production of fractions with substantially constant compositions also makes it possible to automate the progress of this refining.

The resorcinol-rich fraction is conveyed to one or more refining device(s). Before phase 1, the device  
20 is heated above the melting point of resorcinol ( $11^{\circ}\text{C}$ ), i.e., for example, between  $115$  and  $120^{\circ}\text{C}$ .

During phase 1, the body of material is cooled, e.g. to a temperature of between  $40$  and  $90^{\circ}\text{C}$ , over several hours, e.g. over from  $5$  to  $15$  h, which results  
25 in the slow crystallization of the charged mixture.

After phase 1, the product which has remained liquid is withdrawn from the device (phase 2) before passing to phase 3.

Phase 3 consists of the slow reheating of the refining device, optionally begun during phase 2, e.g. up to a temperature of between  $109$  and  $111^{\circ}\text{C}$ , over several hours, e.g. over from  $8$  to  $15$  h. The end of phase 3, which conditions the purity of the product, can be determined either by measuring the  
30 crystallization point or by any other physiochemical analytical technique.

Phase 4 provides for heating of the device to a temperature greater than  $115^{\circ}\text{C}$ , so as to melt the

resorcinol, which is withdrawn in the molten state.

The hydroquinone-rich fractions are treated in the same way. The treatment follows the same phases, apart from the heating/cooling temperatures and times.

5 By way of example:

- preheating between 175 and 180°C
- phase 1, cooling between 90 and 130°C
- phase 1, duration between 5 and 15 h
- phase 3, heating between 170 and 173°C
- 10 - phase 3, duration between 8 and 24 h
- phase 4, heating above 178°C.

The eutectic fractions recovered during the refining can be recycled as a mixture or separately with the hot drainings, preferably in stages (II) and/or (III). It is possible to be induced to recycle them in stage (I), if need be.

Another subject matter of the present invention is a plant which makes possible the implementation of the process described above, comprising:

- 20 (i) an optional distillation column (I) designed to produce catechol at the column top,
- (ii) a distillation column (II), the inlet of which is connected to the bottom of column (I) or receives the crude mixture in the absence of column (I), this column (II) being designed to produce, at the column top, a resorcinol-rich fraction comprising resorcinol, essentially, and hydroquinone,
- 25 (iii) a distillation column (III), the inlet of which is connected to the bottom of column (II), this column (III) being designed to produce, at the column top, a hydroquinone-rich fraction comprising hydroquinone, essentially, and resorcinol,
- 30 (iv) one or more refining devices (IV, V) for providing for the refining of the hydroquinone-rich fraction and/or the
- 35



resorcinol-rich fraction in order to extract hydroquinone and/or resorcinol respectively.

In accordance with the preferred embodiment of the invention, this plant additionally comprises:

- a detarring column (1) designed to produce, at the column top, a detarred fraction and, at the bottom of the column, a tar-rich fraction
- optionally at least one other distillation column (1') fed with the tar-rich fraction originating from the preceding column (1) and designed to produce, at the column top, a detarred fraction and, at the bottom, a tar-rich fraction, the top fraction or fractions of these columns being used to feed column (I) or (II).

The other information and characteristics given above with respect to the process apply directly to the plant according to the invention.

The invention will now be described in more detail with the help of embodiments taken as nonlimiting examples and with reference to the drawing, in which:

- Figure 1 shows the diagram of a first plant in accordance with the invention
- Figure 2 shows the diagram of a second plant in accordance with the preferred embodiment of the invention.

**EXAMPLE 1 (Figure 1):**

1st Distillation column (I):

n (number of theoretical stages) = 30

R (reflux ratio) = 2.7

Column top temperature = 176.4°C

Pressure = 100 mmHg, i.e. 13 332 Pa.

This column (I) is fed continuously with a flow rate of 25.5 kg/h of a mixture to be treated comprising:

- approximately 50% hydroquinone, i.e. approximately

- 10 -

12.75 kg/h

- approximately 15% catechol, i.e. approximately 3.8 kg/h
- approximately 10% resorcinol, i.e. approximately 2.55 kg/h
- approximately 25% tars, i.e. approximately 6.4 kg/h.

A flow rate of approximately 3.8 kg/h is obtained at the column top, which flow rate comprises:

- approximately 99.5% catechol
- approximately 800 ppm hydroquinone
- approximately 40 ppm resorcinol.

A flow rate of approximately 21.7 kg/h is obtained at the column bottom, which flow rate comprises:

- approximately 58.9% hydroquinone (approximately 12.75 kg/h)
- approximately 11.7% resorcinol (approximately 2.55 kg/h)
- approximately 180 ppm catechol
- approximately 29.4% tars (approximately 6.4 kg/h).

#### 2nd Distillation column (II):

n = 30

R = 10

- Column top temperature: 210°C
- Pressure: = 100 mmHg, i.e. 13 332 Pa.

It is fed continuously with the bottom product from the 1st column at a flow rate of approximately 21.7 kg/h.

- A flow rate of approximately 2.56 kg/h of a resorcinol-rich fraction is obtained at the top, which fraction comprises:

- approximately 90% resorcinol (approximately 2.3 kg/h)
- approximately 10% hydroquinone (approximately 0.26 kg/h,
- approximately 1 200 ppm catechol.

A flow rate of approximately 19.14 kg/h of a

mixture is obtained at the bottom, which mixture comprises:

- approximately 65.3% hydroquinone (approximately 12.49 kg/h)
- 5 - approximately 1.3% resorcinol (approximately 0.25 kg/h)
- approximately 33.4% tars (approximately 6.4 kg/h).

3rd (Distillation) detarring column (III):

10 Detarring column: scraped falling film device

Column top temperature: 217°C

Pressure: 100 mmHg, i.e. 13 332 Pa.

This column is fed continuously with the bottom product from the 2nd column at a flow rate of approximately 19.14 kg/h

A flow rate of approximately 9.64 kg/h of a hydroquinone-rich fraction is obtained at the top, which fraction comprises:

- approximately 97.4% hydroquinone (approximately 9.39 kg/h)
- 20 - approximately 2.6% resorcinol (approximately 0.25 kg/h)

A flow rate of approximately 9.5 kg/h of a mixture is obtained at the column bottom, which mixture comprises:

- approximately 32.6% hydroquinone (approximately 3.1 kg/h)
- 25 - approximately 67.4% tars (approximately 6.4 kg/h).

The column bottom product can optionally be redistilled on a detarring column.

Refining:

The refining makes it possible to obtain the pure products from the rich fractions. Drainers of the type with a vertical cylindrical tubular exchanger were used. Similar results will be obtained with other types of devices.

The operating method is as follows:

a) for the hydroquinone-rich fraction:

- Charging: before the charging of approximately 180 kg of hydroquinone-rich fractions, the drainer (V) is preheated to a temperature greater than the melting point of hydroquinone, in this instance to approximately 180°C.
- Cooling: the body of material is slowly cooled by circulation of water to a temperature of approximately 120°C (cooling time approximately 10 h).
- Recovery of the eutectic fraction: the eutectic fraction, which is also known as cold drainings, corresponds to the uncrystallized part of the mixture at the end of cooling and is a mixture of resorcinol and hydroquinone. In the case of these drainers, this fraction can be recovered by simple gravimetric flow and collected in a tank provided for this purpose. This phase lasts approximately 12 hours and takes place with slow reheating of the drainer.
- The reheating of the drainer is continued in order to carry out the hot draining phase. The end of the phase of recovery of the hot drainings is determined by the measurement of the crystallization point of the product which seeps out during this heating phase. This fraction is recovered by simple gravimetric flow and is collected in a tank provided for this purpose. This fraction can either be recycled to the following refining operation or mixed with the cold draining fraction and recycled to the distillation.
- Recovery of the pure hydroquinone: when the crystallization point (171°C) is reached, the flow of the hot drainings is interrupted and the drainer is heated to a temperature of 180°C in order to melt all the hydroquinone. Approximately 65 kg of hydroquinone are recovered with an assay of greater than or equal to 99.5%.

- 13 -

b) For the resorcinol-rich fraction: the processing is carried out in the same way as under a) with the drainer (IV), apart from the essential difference that this time it is the melting temperature of resorcinol which is taken into account, which temperature is 111°C. The heating temperatures are consequently modified.

Charging temperature 120°C  
Cooling to 60°C over approximately 10 h

10 Recovery of the cold draining fraction over approximately 10 h

Reheating from 60 to 110.5°C, the end of this reheating being determined by the measurement of the crystallization point, which determines the final

15 purity of the product.

Heating to 120°C in order to recover the resorcinol: 65 kg with a purity of greater than or equal to 99%.

**EXAMPLE 2: (Figure 2)**

20 In comparison with example 1, two detarring columns (1 and 1') are added upstream of the distillation column (I) to remove at the start the tars present. The first (1) of these columns is fed with the mixture to be treated and the second (1') with the

25 bottom product from the preceding column (1). The streams originating from the two column tops feed the 1st column (I) according to example 1.

Detarring columns

Scraped falling film devices

30 Column top temperature: 174°C  
Pressure: 10 mmHg, i.e. 1 333.2 Pa.

The column (1) is fed continuously with a flow rate of 35 kg/h with a mixture to be treated comprising:

- 35 - approximately 45% hydroquinone, i.e. approximately 15.75 kg/h  
- approximately 7% catechol, i.e. approximately 2.45 kg/h

- approximately 3% resorcinol, i.e. approximately 1.05 kg/h
- approximately 45% tars, i.e. approximately 15.75 kg/h.

5               The top products from the two detarring columns are combined and produce a flow rate of approximately 18.9 kg/h of a detarred fraction comprising:

- approximately 2.45 kg/h catechol
- approximately 15.3 kg/h hydroquinone
- 10 - approximately 1.05 kg/h resorcinol
- approximately 0.1 kg/h tars.

A flow rate of approximately 16.1 kg/h of a tar-rich fraction is obtained at the bottom of the column (1'), which fraction comprises:

- 15 - approximately 15.65 kg/h tars
- approximately 0.45 kg/h hydroquinone

Distillation column (I):

n (number of theoretical stages) = 30

20 R (reflux ratio) = 2.7

Column top temperature = 134°C

Pressure = 10 mmHg, i.e. 1 333.2 Pa.

This column (I) is fed continuously with the flow rate of 18.9 kg/h originating from the detarring.

25               A flow rate of approximately 2.45 kg/h is obtained at the column top, which flow rate comprises:

- approximately 99.5% catechol
- approximately 800 ppm hydroquinone
- approximately 40 ppm resorcinol.

30               A flow rate of approximately 16.45 kg/h is obtained at the column bottom, which flow rate comprises:

- approximately 15.3 kg/h hydroquinone
- approximately 1.05 kg/h resorcinol
- 35 - approximately 180 ppm catechol
- approximately 0.1 kg/h tars.

Distillation column (II):

n = 30

R = 10

Column top temperature: 170°C

5 Pressure: 10 mmHg, i.e. 1 333.2 Pa.

It is fed continuously with the bottom product from the column (I) at a flow rate of approximately 16.45 kg/h.

10 A flow rate of approximately 0.75 kg/h of a resorcinol-rich fraction is obtained at the top, which fraction comprises:

- approximately 0.65 kg/h resorcinol
- approximately 0.1 kg/h hydroquinone
- approximately 1 200 ppm catechol.

15 A flow rate of approximately 15.7 kg/h of a mixture is obtained at the bottom, which mixture comprises:

- approximately 15.2 kg/h hydroquinone
- approximately 0.4 kg/h resorcinol
- 20 - approximately 0.1 kg/h tars.

(Distillation) detarring column (III):

Detarring column: scraped falling film device

Column top temperature: 174.5°C

25 Pressure: 10 mmHg, i.e. 1 333.2 Pa.

This column is fed continuously with the bottom product from the column (II) at a flow rate of approximately 15.7 kg/h.

30 A flow rate of approximately 15.2 kg/h of a hydroquinone-rich fraction is obtained at the top, which fraction comprises:

- approximately 14.8 kg/h hydroquinone
- approximately 0.4 kg/h resorcinol.

35 A flow rate of approximately 0.5 kg/h of a mixture is obtained at the column bottom, which mixture comprises:

- approximately 0.4 kg/h hydroquinone
- approximately 0.1 kg/h tars.

Refining:

The refining is carried out as in example 1.

5 It must be clearly understood that the invention defined by the appended claims is not limited to the specific embodiments indicated in the above description but encompasses the alternative forms thereof which depart neither from the scope nor from the spirit of the present invention.